

Product Weights Chart					
		WHITE or BLACK		REFLECTIVE	
Width	Type	Square Edge	Staple Tab / Tape Tab	Square Edge	Staple Tab / Tape Tab
16"	Single Bubble	3	5	4	6
	Double Bubble	7	9	9	11
24"	Single Bubble	5	7	6	8
	Double Bubble	10	12	12	14
48"	Single Bubble	10	12	12	14
	Double Bubble	20	22	24	26
54"	Single Bubble	12	14	14	16
	Double Bubble	27	29	29	31
66"	Single Bubble	14	16	16	18
	Double Bubble	28	30	32	34
72"	Single Bubble	16	18	18	20
	Double Bubble	30	32	36	38
96"	Single Bubble	21	23	24	26
	Double Bubble	40	42	48	50

Note: All rolls are at 125 lineal feet.
 Weights are in U.S. Pounds

R-Values						
For Bubble Type and Methods of Installation						
	Heat Flow Down		Heat Flow Up		Heat Flow Horizontal	
	Double	Single	Double	Single	Double	Single
Draped over Purlins with 1" airspace						
Reflective/Reflective	R-10	R-10	R-4.1	R-4.0	R-5.5	R-5.0
Reflective/Poly	R-6.5	R-6.0	R-3.4	R-3.2	R-4.1	R-3.9
Attached to the bottom of a 6" or 8" Purlin						
Reflective/Reflective	R-16	R-16	R-4.7	R-4.2	R-5.4	R-4.9
Reflective/Poly	R-12	R-12	R-4.0	R-3.5	R-4.4	R-3.9

R-values include lower air film. Testing and calculations in accordance with ASTM C 236, ASTM STP 1116, and ASHREA Book of Fundamentals and National Bureau of Standards.



PO Box 800
 Auburndale, FL 33823
 Phone: (800) 448-3401
 Fax: (863) 967-0137
 www.fifoil.com